

# Analisa performansi jaringan HSDPA PT Indosat menggunakan metode second carrier : studi kasus node B Cijantung

Ichsan Manzali, author

Deskripsi Lengkap: <https://lib.ui.ac.id/detail?id=20295801&lokasi=lokal>

---

## Abstrak

Meningkatnya kebutuhan data tidak lepas dari meningkatnya penambahan kapasitas jaringan, ketika kapasitas jaringan sudah tidak lagi dapat memenuhi kebutuhan pelanggan maka akan terjadi congesty akibat dari kelebihan kapasitas dari node B, tolok ukur congesty ini dapat dilihat dari power utilisasi, dan pemakaian channel element pada node B. Salah satu metode yang diperlukan untuk mengatasi masalah kelebihan kapasitas dari node B ini ialah dengan mengimplementasikan second carrier HSDPA.

Pada tugas akhir ini akan dilakukan pengukuran pada node B Cijantung PT INDOSAT untuk mengetahui kondisi node B pada saat sebelum dan sesudah implementasi dan dalam keadaan jaringan dengan beban tinggi yaitu malam hari dan pada beban rendah yaitu pagi hari. Second carrier dikonfigurasikan dengan merubah parameter yang terdapat pada OSS. Dari hasil pengukuran menunjukkan bahwa dengan metode second carrier dapat mengurangi waktu transfer dan meningkatkan throughput user serta mengurangi utilisasi daya dan pemakaian CE.

<hr>Increased data requirements cannot be separated from increased network capacity addition, when the network capacity is no longer able to meet customer needs will occur congest result of excess capacity from node B, the benchmark congest can be seen from the power utilization, and the use of channel element at node B . One of the methods required to overcome the problem of excess capacity from node B is to implement the second carrier HSDPA.

Authors performed measurements on Cijantung PT Indosat node B to determine the condition of the node B at the time before and after implementation and the state of the network with high loads of evenings and at low load of the morning. Second carrier is configured by changing the parameters contained in the OSS From the measurement results show that the second method the carrier can reduce the transfer time and increase user throughput and reduce power utilization and use of CE.