Universitas Indonesia Library >> Artikel Jurnal

The development of biochemical oxygen demand sensor using local yeast: candida fukuyamaensis UICC Y-247

Ivandini Tribidasari Anggraningrum, author

Deskripsi Lengkap: https://lib.ui.ac.id/detail?id=20326318&lokasi=lokal

Abstrak

ABSTRACT

In order to shorten the measurement time of biochemical oxygen demand (BOD), a BOD sensor based on yeast metabolism was developed. Local yeast, Indonesian Origin, Candida fukuyamaensis UICC Y-247, was used as a transducer. The yeast was immobilized as a thin film in ag

arose matrix with the auxiliary of Nafion® acting as the membrane for ion exchange process. The film was then attached to gold-modified glassy carbons and used as transducer on the working electrodes. The measurements were conducted by observing the depletion of glucose concentration using multipulse amperometric method and then converte

d to BOD values. Optimum condition was observed in a waiting measurement time of 30 min at an applied potential of 450 mV (vs.

Ag/AgCl). Linearity was shown in glucose concentration range of 0.1?0.5 mM, which was equivalent to BOD concentration range of 10?50 mg/L. A detection limit of 1.13 mg/L BOD could be achieved. Good repeatability was shown by a relative standard deviation (RSD) of

2.7% (n = 15). However, decreasing current response of ~50% was found after 3 days. Comparing to the conventional BOD measurement, this BOD sensor can be used as an alternative method for BOD measurements.