

Perencanaan teknik operasional pada pengelolaan sampah padat fakultas dan fasilitas umum di Universitas Indonesia Depok tahun 2014 = Operational techniques planning of solid waste management at faculties and public facilities in universitas indonesia depok year 2014

Noviaji Joko Priono, author

Deskripsi Lengkap: <https://lib.ui.ac.id/detail?id=20386212&lokasi=lokal>

Abstrak

Tanpa program manajemen sampah yang efektif dan efisien, sampah yang dihasilkan di Universitas Indonesia dapat mengakibatkan dampak terhadap kesehatan dan lingkungan. Tujuan penelitian ini adalah mengembangkan program perencanaan teknik operasional pada pengelolaan sampah di Universitas Indonesia. Lokasi sampel penelitian ini di FISIP, FKM, FT dan Asrama Mahasiswa UI. Peneliti mengukur timbulan sampah gedung, taman, kantin dan jalan selama 8 hari berturut-turut dan melakukan observasi terhadap sistem pengelolaan saat ini. Timbulan sampah padat di UI sebesar 0.023 ± 0.007 kg/orang/hari atau 0.32 ± 0.01 liter/orang/hari, 1.08 ± 0.27 m³/kantin/hari untuk sampah kantin, 2.72 ± 0.58 m³/ha/hari untuk sampah taman dan 0.19 ± 0.008 liter/m/hari untuk sampah jalan. Sistem pemilahan sampah harus dilakukan dari sumbernya hingga proses pengolahan sampah. Di tahun 2014 diperlukan armada pengangkut dengan kapasitas 3 m³ sebanyak empat gerobak motor dan truk kapasitas 6 m³ berjumlah tiga truk.

.....Without effective and efficient of waste management programs, waste generated at the Universitas Indonesia can causes health and environment effects. The purpose of this research to develop a program of operational techniques of waste management planning at the Universitas Indonesia. Primary data taken in May 2014, location of the sample in FISIP, FKM, FT and UI Student Dormitory. Researcher measured waste generation buildings, parks, canteen and road for 8 consecutive days and observe the current management system. Generation of solid waste generated in the UI of 0.023 ± 0.007 kg/person/day or 0.32 ± 0.01 liters/person/day, 1.08 ± 0.27 m³/canteen/day for canteen waste, 0.58 ± 2.72 m³/ha/day for garden waste and 0.19 ± 0.008 liter/m/day to waste the road. Waste collecting system must be done from the source to the sewage treatment process. In 2014 required a fleet carrier with a capacity of 3m³ four motor carts and trucks capacity of 6m³ of three trucks.