

Pembuatan aspal emulsi

Daswiyanto, author

Deskripsi Lengkap: <https://lib.ui.ac.id/detail?id=76772&lokasi=lokal>

Abstrak

Sebagian besar aspal pertamina hanya digunakan sebagai pelapis jalan raya. Hal ini disebabkan terbatasnya jenis dan kelas yang dihasilkan, padahal dengan sedikit modifikasi aspal bisa digunakan diberbagai bidang. Untuk itu perlu dilakukan modifikasi agar aspal pertamina mempunyai nilai tambah yang lebih tinggi. Pada penelitian ini dilakukan modifikasi aspal pertamina dengan mencampurnya dengan aspal buton kemudian dijadikan dalam bentuk emulsi. Penelitian ini dimulai dengan menumbuk dan mengekstrak aspal buton, setelah itu dicampur dengan aspal pertamina dengan berbagai variasi konsentrasi, kemudian diemulsikan dengan sabun (sodium oleat). Aspal emulsi yang terbentuk dilakukan uji spesifikasi yang sesuai dengan aspal emulsi lapisan pelindung logam dan lapisan pelindung atap menurut ASTM. Campuran aspal pertamina dengan aspal buton dapat meningkatkan kualitas aspal emulsi.

<hr><i>Part of pertamina asphalt is only used as road coating. This is because of limited kind and grade produced, whereas by only scanty modifications, it can be used in various sectors. For that reason, modifications are needed so that the pertamina asphalt may possess a higher additional value. In this research, modifications of pertamina asphalt were done by blending with buton asphalt and transformed into emulsion form. This research began with grinding and extracting buton asphalt, then, it was blended with pertamina asphalt by applying various concentrations, and after that, it was emulsified with soap (sodium oleate). The ready-processed emulsion asphalt was examined suitable for protective coating in metal emulsion asphalt and protective coating in roofing as per ASTM specification. The mixture of pertamina asphalt and buton asphalt may 'increase the quality of emulsion asphalt.</i>