

Pemodelan Nilai Koreksi Kebisingan Berdasarkan Komposisi Jenis Kendaraan (Sepeda Motor, Kendaraan Ringan dan Kendaraan Berat) dengan Mempertimbangkan Gradien Jalan (Studi Kasus: Ruas Jalan IR. H. Juanda, Depok, Arah Jalan Raya Bogor) = Modeling Noise Correction Values Based on Vehicle Composition (Motorcycles, Light Vehicles, and Heavy Vehicles) Considering Road Gradient (Case Study: IR. H. Juanda Road Section, Depok, Towards Bogor)

Nurul Hairul Nizah, author

Deskripsi Lengkap: <https://lib.ui.ac.id/detail?id=9999920544393&lokasi=lokal>

Abstrak

Kebisingan merupakan bunyi yang berasal dari kegiatan atau usaha yang tidak di inginkan. Kebisingan di jalan raya bersumber dari aktivitas lalu lintas. Semakin tinggi komposisi jenis kendaraan bermotor, maka dampak kebisingan akan semakin besar. Oleh karena itu, perlu di lakukan pemodelan dengan tujuan untuk memprediksi tingkat kebisingan di suatu lokasi. Penelitian ini dilakukan dengan tujuan untuk mengetahui tingkat kebisingan yang terjadi pada lokasi studi dan memodelkan nilai koreksi kebisingan berdasarkan komposisi jenis kendaraan (sepeda motor, kendaraan ringan dan kendaraan berat). Metode pengumpulan data dilakukan dengan survei secara langsung di lokasi studi untuk mendapatkan data gradien jalan dengan bantuan aplikasi Geotracker, komposisi jenis kendaraan, dan tingkat kebisingan dengan bantuan alat sound level meter. Pelaksanaan survei pada hari kerja (senin-jumat) jam 06:00-17:00 WIB. Berdasarkan Keputusan Menteri Lingkungan Hidup No. KEP-48/MENLH/11/1996, kebisingan yang terjadi di lokasi studi antara 77,1dB(A)-82,3dB(A)telah melebihi ambang batas baku mutu untuk kawasan perdagangan dan jasa.

.....Noise is the sound that comes from unwanted activities or businesses. Noise on the highway originates from traffic activity. The higher the composition of motorized vehicles, the greater the noise impact. Therefore, it is necessary to do modeling with the aim of predicting the noise level at a location. This study was conducted with the aim of knowing the noise level that occurs at the study location and modeling the noise correction value based on the composition of vehicle types (motorcycles, light vehicles and heavy vehicles). The data collection method was carried out by direct survey at the study site to obtain road gradient data with the help of the Geotracker application, the percentage of vehicle types, and noise levels with the help of sound level meters. Surveys are carried out on weekdays (Monday-Friday) 06:00-17:00 WIB. Based on the Decree of the Minister of Environment No. KEP-48/MENLH/11/1996, the noise that occurred at the study location was between 77.1dB(A)-82.3dB(A) which has exceeded the quality standard threshold for trade and service areas.